













| TECHNICAL INFORMATION | | PAGES FOR REFER |
|------------------------------|-----------------------------------|-----------------|
| | | 8 ~ 31 |
| 1. | BEARING MATERIALS | 8 |
| 2. | BEARING TOLERANCES | 8 ~ 11 |
| 3. | BEARING FITS | 12 ~ 17 |
| 4. | BEARING INTERNAL CLEARANCE | 18 |
| 5. | LUBRICATION | 18 ~ 21 |
| 6. | LOAD RATING AND LIFE | 22 ~ 28 |
| 7. | BEARING HANDLING | 29 ~ 31 |
| | | |

PRODUCT INFORMATION



| | | PAGES FOR REFER |
|---|---|-----------------|
| | | 33~165 |
| NEEDLE ROLLER AND CAGE ASSEMBLIES | | 33~43 |
|  | DRAWN CUP NEEDLE ROLLER BEARINGS | 45~57 |
|  | MACHINE D-RING NEEDLE ROLLER BEARINGS | 59~86 |
|  | THRUST ROLLER BEARINGS | 87~94 |
|  | COMPLEX BEARINGS | 95~105 |
|  | ROLLER FOLLOWERS | 107~119 |
|  | CAM FOLLOWERS | 121~129 |
|  | COMPONENTS | 131~144 |
|  | ONE-WAY CLUTCHES | 145~148 |
|  | MACHINE D-RING NEEDLE ROLLER BEARINGS, SEPARABLE | 149~159 |
|  | SEALS | 161~165 |
| | | |